

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
25 August 2005 (25.08.2005)

PCT

(10) International Publication Number
WO 2005/078845 A3

(51) International Patent Classification:
H01M 8/04 (2006.01) *H01M 16/00* (2006.01)

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(21) International Application Number:
PCT/JP2005/002519

(22) International Filing Date:
10 February 2005 (10.02.2005)

(25) Filing Language: English

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(26) Publication Language: English

(30) Priority Data:
2004-039884 17 February 2004 (17.02.2004) JP

(71) Applicant (for all designated States except US): NISSAN MOTOR CO., LTD. [JP/JP]; 2, Takara-cho, Kanagawa-ku, Yokohama-shi, Kanagawa, 2210023 (JP).


Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

(88) Date of publication of the international search report:
20 April 2006

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: FUEL CELL SYSTEM



(57) Abstract: A fuel cell system and a related operating method are disclosed. The system includes a fuel cell body 1 having an anode electrode supplied with fuel gas containing hydrogen and a cathode electrode supplied with oxidizer gas, a catalyst degradation-suppressing means operative to interrupt supplying oxidizer gas to the cathode electrode after disconnecting the external load from the fuel cell body 1 and allow a load current, generated by the fuel cell body 1, to be extracted by an internal load 26 while supplying fuel gas to the anode electrode, a hydrogen supply stop means operative to interrupt a supply of fuel gas to the anode electrode during a period in which the load current is extracted by the internal load, and load current control means controlling a target load current such that after the supply of fuel gas to the anode electrode is stopped, a pressure inside the anode electrode is maintained at a target pressure.

WO 2005/078845 A3